



DIMENSIONS (mm)

LAND PATTERNS (mm)

Part No.	A	B	C	D	E	F
JPRD 0315	3.8 ± 0.3	3.8 ± 0.3	1.8 Max.	1.60	1.20	4.50

SERIES LIST

No.	Part No.	L (μH)	Test Frequency (KHz)	RDC Max. (Ω)	IDC Max. (A)
1	JPRD 0315-3R3M -	3.3	100	0.085	1.10
2	JPRD 0315-3R9M -	3.9	100	0.081	0.75
3	JPRD 0315-4R7M -	4.7	100	0.105	0.90
4	JPRD 0315-5R6M -	5.6	100	0.102	0.62
5	JPRD 0315-6R8M -	6.8	100	0.170	0.73
6	JPRD 0315-8R2M -	8.2	100	0.140	0.51
7	JPRD 0315-100M -	10	100	0.210	0.55
8	JPRD 0315-120M -	12	100	0.205	0.42
9	JPRD 0315-150M -	15	100	0.295	0.45
10	JPRD 0315-180M -	18	100	0.327	0.34
12	JPRD 0315-220M -	22	100	0.430	0.40
13	JPRD 0315-270M -	27	100	0.470	0.28
14	JPRD 0315-330M -	33	100	0.675	0.32
15	JPRD 0315-390M -	39	100	0.700	0.24
16	JPRD 0315-470M -	47	100	0.775	0.21

Tolerance : M = ± 20% , M tolerance is standard.

: Revision of specification

PACKAGE

Type	JPRD 0315
Q'TY/Reel	2,000

