



## DIMENSIONS (mm)

Part No.	A	B	C	D	E	F
JPRD 0604	6.7 ± 0.3	6.7 ± 0.3	4.0 Max.	2.65	2.00	7.30

## SERIES LIST

No.	Part No.	L ( $\mu$ H)	Test Frequency (KHz)	RDC Max. ( )	IDC Max. (A)
1	JPRD 0604-3R3M -	3.3	10	0.020	3.50
2	JPRD 0604-5R0M -	5.0	10	0.024	2.90
3	JPRD 0604-6R2M -	6.2	10	0.027	2.50
4	JPRD 0604-7R4M -	7.4	10	0.031	2.30
5	JPRD 0604-8R7M -	8.7	10	0.034	2.20
6	JPRD 0604-100M -	10	10	0.038	2.00
7	JPRD 0604-120M -	12	10	0.053	1.70
8	JPRD 0604-150M -	15	10	0.057	1.60
9	JPRD 0604-180M -	18	10	0.092	1.50
10	JPRD 0604-220M -	22	10	0.096	1.30
12	JPRD 0604-270M -	27	10	0.109	1.20
13	JPRD 0604-330M -	33	10	0.124	1.10
14	JPRD 0604-390M -	39	10	0.138	1.00
15	JPRD 0604-470M -	47	10	0.155	0.95
16	JPRD 0604-560M -	56	10	0.202	0.85
17	JPRD 0604-680M -	68	10	0.234	0.75
18	JPRD 0604-820M -	82	10	0.324	0.70
19	JPRD 0604-101M -	100	10	0.358	0.65

Tolerance : M = ± 20% , M tolerance is standard.

: Revision of specification

## PACKAGE

Type	JPRD 0604
Q'TY/Reel	1,000