



DIMENSIONS (mm)

Part No.	A	B	C	D	E	F
JPRH 0704	7.3 ± 0.2	7.3 ± 0.2	4.5 Max.	1.60	4.80	2.20

SERIES LIST

No.	Part No.	L (μH)	Test Frequency (KHz)	RDC Max. ()	IDC Max. (A)
1	JPRH 0704-100M -	10	1	0.049	1.84
2	JPRH 0704-120M -	12	1	0.058	1.71
3	JPRH 0704-150M -	15	1	0.081	1.47
4	JPRH 0704-180M -	18	1	0.091	1.31
5	JPRH 0704-220M -	22	1	0.110	1.23
6	JPRH 0704-270M -	27	1	0.150	1.12
7	JPRH 0704-330M -	33	1	0.170	0.96
8	JPRH 0704-390M -	39	1	0.230	0.91
9	JPRH 0704-470M -	47	1	0.260	0.88
10	JPRH 0704-560M -	56	1	0.350	0.75
11	JPRH 0704-680M -	68	1	0.380	0.69
12	JPRH 0704-820M -	82	1	0.430	0.61
13	JPRH 0704-101M -	100	1	0.610	0.60
14	JPRH 0704-121M -	120	1	0.660	0.52
15	JPRH 0704-151M -	150	1	0.880	0.46
16	JPRH 0704-181M -	180	1	0.980	0.42
17	JPRH 0704-221M -	220	1	1.170	0.36
18	JPRH 0704-271M -	270	1	1.640	0.34
19	JPRH 0704-331M -	330	1	1.860	0.32
20	JPRH 0704-391M -	390	1	2.850	0.29
21	JPRH 0704-471M -	470	1	3.010	0.26
22	JPRH 0704-561M -	560	1	3.620	0.23
23	JPRH 0704-681M -	680	1	4.630	0.22
24	JPRH 0704-821M -	820	1	5.200	0.20
25	JPRH 0704-102M -	1000	1	6.000	0.18

Tolerance : M ± 20% , M tolerance is standard.

: Revision of specification

PACKAGE

Type	JPRH 0704
Q'TY/Reel	1,000