



DIMENSIONS (mm)

Part No.	A	B	C	D	E	F
JPRH 1205	12.0 ± 0.3	12.0 ± 0.3	6.0 Max.	2.80	7.00	5.40

SERIES LIST

No.	Part No.	L (μH)	Test Frequency (MHz)	RDC Max. ()	IDC Max. (A)
1	JPRH 1205-1R3M -	1.3	7.96	0.012	8.00
2	JPRH 1205-2R1M -	2.1	7.96	0.014	7.00
3	JPRH 1205-3R1M -	3.1	7.96	0.017	6.00
4	JPRH 1205-4R4M -	4.4	7.96	0.020	5.00
5	JPRH 1205-5R8M -	5.8	7.96	0.021	4.40
6	JPRH 1205-7R5M -	7.5	7.96	0.024	4.20
7	JPRH 1205-100M -	10	1K	0.025	4.00
8	JPRH 1205-120M -	12	1K	0.027	3.50
9	JPRH 1205-150M -	15	1K	0.030	3.30
10	JPRH 1205-180M -	18	1K	0.034	3.00
11	JPRH 1205-220M -	22	1K	0.036	2.80
12	JPRH 1205-270M -	27	1K	0.051	2.30
13	JPRH 1205-330M -	33	1K	0.057	2.10
14	JPRH 1205-390M -	39	1K	0.068	2.00
15	JPRH 1205-470M -	47	1K	0.075	1.80
16	JPRH 1205-560M -	56	1K	0.110	1.70
17	JPRH 1205-680M -	68	1K	0.120	1.50
18	JPRH 1205-820M -	82	1K	0.140	1.40
19	JPRH 1205-101M -	100	1K	0.160	1.30
20	JPRH 1205-121M -	120	1K	0.170	1.10
21	JPRH 1205-151M -	150	1K	0.230	1.00
22	JPRH 1205-181M -	180	1K	0.290	0.90
23	JPRH 1205-221M -	220	1K	0.400	0.80
24	JPRH 1205-271M -	270	1K	0.460	0.75
25	JPRH 1205-331M -	330	1K	0.510	0.68
26	JPRH 1205-391M -	390	1K	0.690	0.65
27	JPRH 1205-471M -	470	1K	0.770	0.58
28	JPRH 1205-561M -	560	1K	0.860	0.54
29	JPRH 1205-681M -	680	1K	1.200	0.48
30	JPRH 1205-821M -	820	1K	1.340	0.43
31	JPRH 1205-102M -	1000	1K	1.530	0.40

Tolerance : M ± 20% , M tolerance is standard.

: Revision of specification

PACKAGE

Type	JPRH 1205
Q'TY/Reel	500