



Unit: mm

Part No.	A	B	C	D	E	F	G	H	I
JWI 322522T	3.2 ± 0.3	2.5 ± 0.2	2.2 ± 0.2	0.6 ref	0.2 min	1.9 ± 0.1	1.2	2.0	2.0

No.	Part No.	Inductance (μ H)	Q Min.	Test Frequency (MHz)	SRF Min. (MHz)	RDC Max. (Ω)	IDC Max. (mA)
1	JWI 322522T-10NJ	0.010	15	100	2500	0.13	450
2	JWI 322522T-12NJ	0.012	17	100	2300	0.14	450
3	JWI 322522T-15NJ	0.015	19	100	2100	0.16	450
4	JWI 322522T-18NJ	0.018	21	100	1900	0.18	450
5	JWI 322522T-22NJ	0.022	23	100	1700	0.20	450
6	JWI 322522T-27NJ	0.027	23	100	1500	0.22	450
7	JWI 322522T-33NJ	0.033	25	100	1400	0.24	450
8	JWI 322522T-39NJ	0.039	25	100	1300	0.27	450
9	JWI 322522T-47NJ	0.047	26	100	1200	0.30	450
10	JWI 322522T-56NJ	0.056	26	100	1100	0.33	450
11	JWI 322522T-68NJ	0.068	27	100	1000	0.36	450
12	JWI 322522T-82NJ	0.082	27	100	900	0.40	450
13	JWI 322522T-R10J	0.10	28	100	700	0.44	450
14	JWI 322522T-R12J	0.12	30	25.2	500	0.22	450
15	JWI 322522T-R15J	0.15	30	25.2	450	0.25	450
16	JWI 322522T-R18J	0.18	30	25.2	400	0.28	450
17	JWI 322522T-R22J	0.22	30	25.2	350	0.32	450
18	JWI 322522T-R27J	0.27	30	25.2	320	0.36	450
19	JWI 322522T-R33J	0.33	30	25.2	300	0.40	450
20	JWI 322522T-R39J	0.39	30	25.2	250	0.45	450
21	JWI 322522T-R47J	0.47	30	25.2	220	0.50	450
22	JWI 322522T-R56J	0.56	30	25.2	180	0.55	450
23	JWI 322522T-R68J	0.68	30	25.2	160	0.60	450
24	JWI 322522T-R82J	0.82	30	25.2	140	0.65	450
25	JWI 322522T-1R0J	1.0	30	7.96	120	0.70	400
26	JWI 322522T-1R2J	1.2	30	7.96	100	0.75	390
27	JWI 322522T-1R5J	1.5	30	7.96	85	0.85	370
28	JWI 322522T-1R8J	1.8	30	7.96	80	0.90	350
29	JWI 322522T-2R2J	2.2	30	7.96	75	0.10	320
30	JWI 322522T-2R7J	2.7	30	7.96	70	1.10	290

No.	Part No.	Inductance (μ H)	Q Min.	Test Frequency (MHz)	SRF Min. (MHz)	RDC Max. (Ω)	IDC Max. (mA)
31	JWI 322522T-3R3J	3.3	30	7.96	60	1.2	260
32	JWI 322522T-3R9J	3.9	30	7.96	55	1.3	250
33	JWI 322522T-4R7J	4.7	30	7.96	50	1.5	220
34	JWI 322522T-5R6J	5.6	30	7.96	45	1.6	200
35	JWI 322522T-6R8J	6.8	30	7.96	40	1.8	180
36	JWI 322522T-8R2J	8.2	30	7.96	35	2.0	170
37	JWI 322522T-100J	10	30	2.52	30	2.1	150
38	JWI 322522T-120J	12	30	2.52	20	2.5	140
39	JWI 322522T-150J	15	30	2.52	20	2.8	130
40	JWI 322522T-180J	18	30	2.52	20	3.3	120
41	JWI 322522T-220J	22	30	2.52	20	3.7	110
42	JWI 322522T-270J	27	30	2.52	18	5.0	80
43	JWI 322522T-330J	33	30	2.52	17	5.6	70
44	JWI 322522T-390J	39	30	2.52	16	6.4	65
45	JWI 322522T-470J	47	30	2.52	15	7.0	60
46	JWI 322522T-560J	56	30	2.52	13	8.0	55
47	JWI 322522T-680J	68	30	2.52	12	9.0	50
48	JWI 322522T-820J	82	30	2.52	11	10	45
49	JWI 322522T-101J	100	20	0.796	10	10	40
50	JWI 322522T-121J	120	20	0.796	9	11	70
51	JWI 322522T-151J	150	20	0.796	7	15	65
52	JWI 322522T-181J	180	20	0.796	7	17	60
53	JWI 322522T-221J	220	20	0.796	6	21	50
54	JWI 322522T-271J	270	20	0.796	5	28	45
55	JWI 322522T-331J	330	20	0.796	5	34	40

* Tolerance : J = \pm 5%

■ PACKAGE

Type	JWI 322522T
Q'TY/Reel	2000
Reel size	7"