



Radial Leaded PTC Resettable Fuse : FRG Series

1. Summary

- (a) **RoHS Compliant (Lead Free) Product**
- (b) **Applications : Wide variety of electronic equipment**
- (c) **Product Features : Very Low resistance, Very High hold current, Solid state, Radial leaded product ideal for up to 16V**
- (d) **Operation Current : 3.0A~14.0A**
- (e) **Maximum Voltage : 16V**
- (f) **Temperature Range : -40°C to 85°C**

2. Agency Recognition

- UL : File No. E211981**
- C-UL: File No. E211981**
- TÜV: File No. R 50004084**

3. Electrical Characteristics (23°C)

Part Number	Hold Current	Trip Current	Max.Time to trip	Maximum Current	Rated Voltage	Typical Power	Resistance Tolerance	
							Rmin	R1max
	I _H , A	I _T , A	at 5x I _H	I _{MAX} , A	V _{MAX} , Vdc	P _d , W	ohms	ohms
FRG300-16F	3.0	5.1	2.0	100	16	2.3	0.034	0.105
FRG400-16F	4.0	6.8	3.5	100	16	2.4	0.020	0.063
FRG500-16F	5.0	8.5	3.6	100	16	2.6	0.014	0.044
FRG600-16F	6.0	10.2	5.8	100	16	2.8	0.009	0.033
FRG700-16F	7.0	11.9	8.0	100	16	3.0	0.006	0.021
FRG800-16F	8.0	13.6	9.0	100	16	3.0	0.005	0.018
FRG900-16F	9.0	15.3	12.0	100	16	3.3	0.004	0.015
FRG1000-16F	10.0	17.0	12.5	100	16	3.3	0.003	0.012
FRG1100-16F	11.0	18.7	13.5	100	16	3.7	0.003	0.010
FRG1200-16F	12.0	20.4	16.0	100	16	4.2	0.002	0.009
FRG1400-16F	14.0	23.8	20.0	100	16	4.6	0.002	0.008

I_H=Hold current-maximum current at which the device will not trip at 23°C still air.
I_T=Trip current-minimum current at which the device will always trip at 23°C still air.
V_{MAX}=Maximum voltage device can withstand without damage at its rated current.
I_{MAX}= Maximum fault current device can withstand without damage at rated voltage (V max).
P_d=Typical power dissipated from device when in the tripped state in 23°C still air environment.
R_{MIN}=Minimum device resistance at 23°C.
R_{1MAX}=Maximum device resistance at 23°C 1 hour after tripping .

Physical specifications:

Lead material: FRG300-16F~FRG1100-16F Tin plated copper,20 AWG.

FRG1200-16F~FRHG400-16F Tin plated copper,18 AWG.


Soldering characteristics:MIL-STD-202, Method 208E.

Insulating coating:Flame retardant epoxy ,meet UL-94V-O requirement.

NOTE : Specification subject to change without notice.



4. Production Dimensions (millimeter)



Lead Size

FRG300-16F~FRG1100-16F

Φ 0.81 mm Diameter

20AWG

Lead Size


FRG1200-16F~FRG1400-16F

Φ 1.0 mm Diameter

18AWG

Part Number	A	B	C	D	E	F
	Maximum	Maximum	Typical	Minimum	Maximum	Typical
FRG300-16F	7.1	11.0	5.1	7.6	3.0	1.2
FRG400-16F	8.9	12.8	5.1	7.6	3.0	1.2
FRG500-16F	10.4	14.3	5.1	7.6	3.0	1.2
FRG600-16F	10.7	17.1	5.1	7.6	3.0	1.2
FRG700-16F	11.2	19.7	5.1	7.6	3.0	1.2
FRG800-16F	12.7	20.9	5.1	7.6	3.0	1.2
FRG900-16F	14.0	21.7	5.1	7.6	3.0	1.2
FRG1000-16F	16.5	24.1	5.1	7.6	3.0	1.2
FRG1100-16F	17.5	26.0	5.1	7.6	3.0	1.2
FRG1200-16F	17.5	28.0	10.2	7.6	3.6	1.4
FRG1400-16F	27.9	27.9	10.2	7.6	3.6	1.4

5. Thermal Derating Curve




NOTE : Specification subject to change without notice.



6. Typical Time-To-Trip at 23°C

- A=FRG300-16F
- B=FRG400-16F
- C=FRG500-16F
- D=FRG600-16F
- E=FRG700-16F
- F=FRG800-16F
- G=FRG900-16F
- H=FRG1000-16F
- I=FRG1100-16F
- J=FRG1200-16F
- K=FRG1400-16F





7. Material Specification

Lead material : FRG300-16F~FRG1100-16F Tin plated copper, 20 AWG.
 FRG1200-16F~FRG1400-16F Tin plated copper, 18 AWG.
 Soldering characteristics:MIL-STD-202, Method 208E.
 Insulating coating: Flame retardant epoxy, meets UL-94V-0 requirement.

8. Part Numbering and Marking System


Part Numbering System

FRG □ □ □ - □ □ □ F



Example

Part Marking System



Warning: -Operation beyond the specified maximum ratings or improper use may result in damage and possible electrical arcing and/or flame.
 -PPTC device are intended for occasional overcurrent protection. Application for repeated overcurrent condition and/or prolonged trip are not anticipated.
 - Avoid contact of PPTC device with chemical solvent. Prolonged contact will damage the device performance

NOTE : Specification subject to change without notice.